

The Kytola flowmeter model L is a cost-effective solution for purge applications.



Applications

- Nitrogen, water, and air purging monitoring

Features

- Acrylic, Trogamid or Grilamid flowtube
- Integral needle valve
- Several flow ranges and scales
- O-ring seals

Options

- Plug resistant valve, for service in applications where large contaminants are found in the media
- Constant flow regulator (Model 2850 or 3630)
- Calibration for non-standard gases and liquids
- Special scale markings
- Viton or EPDM seals
- Hand knob

Technical Specifications

	LH	LT	LR
Flowtube / body	Acrylic (PMMA)	Trogamid-T	Grilamid TR55
Seals	Nitrile	Nitrile	Nitrile
Connectors	AISI 316	AISI 316	AISI 316
Valve assembly	AISI 316	AISI 316	AISI 316
Max. pressure	440 psi @ 85°F (30°C)	440 psi @ 85°F (30°C)	440 psi @ 95°F (35°C)
Max. temperature	167°F (75°C) @ 290 psi	158°F (70°C) @ 290 psi	176°F (80°C) @ 290 psi
Connections	1/4" NPT	1/4" NPT	1/4" NPT
Accuracy	± 10% F.S. H ₂ O @ 68°F (20°C)	± 10% F.S. H ₂ O @ 68°F (20°C)	± 10% F.S. H ₂ O @ 68°F (20°C)
Weight	0.6 lb (300 g)	0.6 lb (300 g)	0.6 lb (300 g)

Order Guide

L	x	-	xx	x	-	x	
							FLOWTUBE
	H						Acrylic
	R						Grilamid
	T						Trogamid
							FLOWRANGE
							WATER
							AIR
							USGPH
							LPM
							SCFH
							NLPM
							(N)
							(A)
							(V)
							(R)
	4K						0.28 18 MLPM 2 0.9
	4A						0.47 30 MLPM 2.8 1.2
	4B						0.8 55 MLPM 4 1.8
	4C						1.27 80 MLPM 6 2.5
	5K						2 0.13 14 6
	5A						3.6 0.2 16 7
	5B						5.5 0.3 24 10
	5C						8.5 0.5 32 14
	8M						17 1 70 30
	8P						26 1.6 120 50
	8S						40 2.6 200 85
	8R						45 3 240 100
							SCALE
	A						LPM water (MLPM)
	D						Relative scale 1 - 10
	L						Dual scale GPH water / SCFH air
	M						Dual scale LPM water / NLPM air
	N						USGPH water
	R						NLPM air (101.3 Kpa @ 20°C)
	V						SCFH air (14.7 psig @ 70°F)
							OPTIONS
	H						Hand adjusting knob
	R						BSP 1/4" connections
	V						Viton seals
	Y						EPDM seals
	2850-NL						Constant flow regulator, AISI 316, 1/4" NPT, With pipe connection kit
	3630A-N						Constant flow regulator, aluminium, 1/4" NPT
	3630H-N						Constant flow regulator, AISI 316, 1/4" NPT

esko INDUSTRIES Limited

Canada: 3480 Gardner Court, Burnaby BC, V5G 3K4
 USA: PO Box 5547, Bellingham WA, 98227-5547
 Toll free: 1.800.665.ESKO (3756)
 Phone: 604.294.ESKO (3756)
 Fax: 604.294.3727
 Email: info@eskoindustries.com
 Internet: www.eskoindustries.com